



FARRELL TEXTURE COAT

Product Data Sheet

Superior Cementitious Coating For Concrete & Masonry

DESCRIPTION:

FARRELL TEXTURE COAT is a superior cementitious coating for concrete and masonry. It provides a protective and waterproof surface while eliminating the rubbing process. Spray or Brush Applied available in white (#1993) or pearl gray (#1994). Trowel Grade (#1989) available in pearl gray.

WHEN/WHERE TO USE:

Waterproofing and finishing all concrete & masonry surfaces Fills and seals pores, voids, and honeycombing in concrete in one application Can be used on highway bridge parapets and structure supports Use to waterproof swimming pools, cisterns and water reservoirs

ADVANTAGES:

- Eliminates rubbing
- Trowel, spay or brush applied
- Outlasts all paints
- Breathes won't blister
- Exceptional filling characteristics
- Provides waterproofing
- Withstands continuous freeze / thaw cycles

TECHNICAL DATA

COMPRESSION	4200 PSI AFTER 28 DAYS	
IMPACT	22 INCH POUNDS	
ABSORPTION	2.3% AFTER 24 HOURS	
ABRASION	PASSED 2400 LITER SAND ABRASION	
RESISTANCE	NO PENETRATION FOR 12 HOURS @ 100 MPH	
FREEZE / THAW	PASSED 50 CYCLES	
FUNGUS GROWTH RESISTANCE	EXCELLENT	
SALT SPRAY RESISTANCE	EXCELLENT	
CEMENT BASED WATERPROOF COATING		
MN DOT APPROVED SPECIAL SURFACE FINISH SYSTEM		

TYPICAL YIELD:

For finishing concrete / bridge parapets etc. - approximately 4 sq. ft. per lb. Two coat applications: 80 - 120 sq. ft. per 50lb. bag. Uneven surfaces or thicker covering, allow 1 sq. ft. per lb. at 1/8" thick.

PACKAGING: 50 lb. bag

SURFACE PREPARATION:

Surfaces to be coated must be clean and free of chemical deposits, dirt, form oils, efflorescence, grease, oil, paint, etc. Do not apply at temperatures below 40° F or if temperature is expected to fall below 40° F within 24 hours.

MIXING:

Mix one part Farrell Bonding Agent with 2 - $2\frac{1}{2}$ parts clean water. Mix Farrell Texture Coat to a creamy consistency for spray or brush-on applications. 50lb. bag requires a mixture of 1/2 gallon Farrell Bonding Agent and 6 - 7 quarts of water. Weather and humidity conditions may require more or less water. Remix every 5 minutes to prevent product from taking on initial set. Trowel (thicker) applications require less water.

APPLICATION:

- Spray Applied: Use plaster or hopper type guns.
- Trowel Applied: Use trowel grade on rough or marred (uneven) surfaces for leveling as well as finishing.
- Brush Applied: Recommended for smaller areas where surfaces are leveled.

CLEAN UP:

Typically water will satisfactorily clean tools after using Farrell Texture Coat. If the material has begun to harden, warm soapy water may be helpful for cleaning hands and tools.

Farrell Equipment & Supply

EAU CLAIRE 715-835-4334 800-533-0909 Fax: 715-835-4356 1510 N. Hastings Way Eau Claire, WI 54703

APPLETON
920-903-1985
Fax: 920-903-8278
1002 Truman Street
Kimberly, WI 54136

La Crosse, WI 54603

MADISON 608-222-53 888-533-79 Fax: 608-22 6809 Mangrove Lane Monona, WI 53713

	The last	
	Y	and the
	- AL	
1 .	10	
A	10.	
1 Same	4	to a start

Weston, WI 54476

©Farrell E	quipment &	& Supply	Со.,	Inc. •	2017	Version	2.0

LA CROSSE	
608-796-9300	
888-533-0909	
Fax: 608-796-9435	
508 Monitor Street	
0 0 marca 14/1 E 4600	



WARRANTY:

Seller warrants that its product will conform to and perform in accordance with the product specifications. The foregoing warranty is in lieu of all other warranties, express or implied, including, but not limited to, those including merchantability and fitness for a particular purpose. Because of the difficulty in ascertaining and measuring damages hereunder, it is agreed that, the sellers liability to the buyer at no point for any particular project shall exceed the total purchase price of said product.

WARNING:

This product contains Portland cement. Contact with cement, freshly mixed concrete, or mortar can cause sever burns. The cementitious materials mixed onsite are alkaline in nature and on contact with water may irritate the eyes and skin. If contact with eyes occurs, flood eyes repeatedly with clean water and see a physician immediately. Do not rub eyes. Wash hands thoroughly after handling or before eating. Do not take internally. This product may contain silica. Inhaled silica dust may cause respiratory or other health problems.

Co., Inc.		
I	ROCHESTER	WAUSAU
372	507-252-0234	715-355-8300
909	888-533-8909	800-933-5939
22-5405	Fax: 507-252-0222	Fax: 715-298-1662
prove Lane	1635 3rd Avenue S.E.	7405 Commerce Drive

Rochester, MN 55904