



**SAFETY DATA SHEET**

Date Revised: 3/4/14

Farrell Equipment & Supply Co., Inc.  
1510 N. Hastings Way Eau Claire, WI 54703  
715-835-4334 www.farrellequipment.com

Date Printed: 2/16/16

===== SECTION 1 - IDENTIFICATION =====

MANUFACTURER: SIERRA CORP/TK PRODUCTS EMERGENCY PHONE: 1-800-424-9300  
ADDRESS : 11400 WEST 47TH STREET INFORMATION PHONE: (952)938-7223  
MINNETONKA, MN 55343 NAME OF PREPARER : Safety Director  
PRODUCT NAME: FARREL FORM RELEASE AGENT  
PRODUCT CODE: TK-FFRA

===== SECTION 2 - HAZARDS IDENTIFICATION =====

HAZARD RISK CLASSIFICATION  
SIGNAL WORD: DANGER  
PICTOGRAM:  
GHS08 - HEALTH HAZARD

HAZARD CLASS HAZARD CATEGORY  
ASPIRATION HAZARD CATEGORY 1

HAZARD STATEMENTS:  
H304 May be fatal if swallowed or enters airways  
PRECAUTIONARY STATEMENTS:  
PREVENTION:  
P101 If medical advice is needed, have product container or label at hand. Keep out of reach of children.  
P102 Keep out of reach of children.

RESPONSE:  
P301+P310 If swallowed: Immediately call a Poison Center / doctor.  
STORAGE:  
P405 Store locked up.  
DISPOSAL:  
P501 Store separately. Dispose of contents/ container in accordance with local/ regional/national /international regulations.

===== SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS =====

COMPONENT	CAS NUMBER	WEIGHT PERCENT	EXPOSURE LIMITS		
			OSHA PEL	ACGIH TLV	OTHER
Hydrotreated Petroleum Distillates	64742-53-6	90-100			5 MG/M3

PRIMARY ROUTES OF EXPOSURE:  
Skin contact.  
EFFECTS OF ACUTE EXPOSURE:  
EYES: Direct contact with eyes may cause irritation.  
SKIN: Prolonged or repeated contact may cause irritation. INHALATION: Inhalation of vapor or mist can cause irritation of nose, throat and lungs and lead to headaches and nausea.  
INGESTION: Not an anticipated route of exposure. Small amounts are not expected to be harmful.  
CHRONIC HEALTH EFFECTS:  
No anticipated chronic effects. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:  
No known effects on other illnesses.

===== SECTION 4 - FIRST AID MEASURES =====

EYES: Flush with large amounts of water for 15 minutes, lifting upper and lower eyelids. If irritation persists seek

# SAFETY DATA SHEET

Page: 2 of 4  
Process Time: 7:07 am

Date Revised: 3/4/14

Date Printed: 2/16/16

medical attention.

SKIN CONTACT: Wash contaminated area with soap and water. Remove and launder contaminated clothing.

INGESTION: If a large amount is ingested, give water or milk and induce vomiting. Seek medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. If breathing has stopped administer artificial respiration. Seek medical attention if condition persists.

## SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: Greater than 200 F

METHOD USED: SETA

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.8

UPPER: 7

### EXTINGUISHING MEDIA:

This material will not burn in its liquid state unless heated above its flash point. Dried films may burn and can be extinguished by water spray, foam, dry chemical or carbon dioxide.

### SPECIAL FIREFIGHTING PROCEDURES:

Persons exposed to products of combustion should wear self-contained breathing apparatus and full protective equipment. Isolate danger area, keep unauthorized personnel out.

### UNUSUAL FIRE AND EXPLOSION HAZARDS:

There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool these containers.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Do not let uncured spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear appropriate protective equipment.

## SECTION 7 - HANDLING AND STORAGE

### HANDLING INFORMATION:

Employees who come in contact with this material must be trained in accordance to 1910.1200 of the Hazard Communication Standard. Wear chemical resistant gloves and protective clothing to minimize contact. The use of respiratory protection is advised when spraying because of mist and dust overspray.

### STORAGE INFORMATION:

Keep containers tightly closed. Use and store material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Post "No smoking or open flame" sign. Store only in approved containers. Keep away from incompatible materials (see section 10). Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

### OTHER PRECAUTIONS:

All empty containers should be disposed of in an environmentally safe manner in accordance with all governmental regulations.

## SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

### RESPIRATORY PROTECTION:

No special requirements under normal use conditions. In confined areas, or areas with poor ventilation, engineering controls should be used to minimize exposure. Use NIOSH/MSHA approved respirator if conditions warrant.

### VENTILATION:

General room ventilation is adequate.

### PROTECTIVE GLOVES:

Prevent prolonged or repeated contact by wearing chemical resistant gloves and other appropriate protective clothing. Launder contaminated clothing before reuse.

### EYE PROTECTION:

Wear safety glasses to reduce eye contact potential. Chemical safety goggles (ANSI Z87.1 or approved equivalent) are appropriate if splashing is likely. Eye washes must be available where eye contact can occur.

### OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

A source of clean water should be available for flushing eyes and skin. Showers should be available if larger spills are possible.

### WORK/HYGIENIC PRACTICES:

Efforts should be made to minimize contact and spills. Always wash hands before eating, drinking, or smoking. Clean up

# SAFETY DATA SHEET

Page: 3 of 4  
Process Time: 7:07 am

Date Revised: 3/4/14

Date Printed: 2/16/16

spills promptly. Follow OSHA and company guidelines.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid  
ODOR: Amine or ammonia odor  
SPECIFIC GRAVITY (H2O=1): .88  
BOILING RANGE:  
COATING V.O.C.: 0 g/l (0.0 lb/gl )

COLOR: Clear(Water white)  
SOLUBILITY IN WATER: Dilutable  
VAPOR DENSITY: Heavier than air.  
EVAPORATION RATE: Slower than nBuAc

## SECTION 10 - STABILITY AND REACTIVITY DATA

STABILITY:  
Stable under normal conditions and handling.

CONDITIONS TO AVOID:  
None known

INCOMPATIBILITY (MATERIALS TO AVOID):  
None known. Materials which are not compatible with water or ordinary organics will not be compatible with this material.

### HAZARDOUS DECOMPOSITION OR BYPRODUCTS:

Combustion may liberate toxic byproducts such as carbon dioxide, and carbon monoxide, various oxides of carbon and nitrogen. Thermal decomposition may liberate acrylic monomers and ammonia.

### HAZARDOUS POLYMERIZATION:

Will not occur.

## SECTION 11 - TOXICOLOGICAL INFORMATION

SENSITIZATION:  
None known.

CARCINOGENICITY:  
There is no data available to indicate any components present at greater than 0.1% may present a carcinogenic hazard.

REPRODUCTIVE TOXICITY:  
There is no data available to indicate any components present at greater than 0.1% may present reproductive toxicity.

TERATOGENICITY (BIRTH DEFECTS):  
There is no data available to indicate any components present at greater than 0.1% may cause birth defects.

MUTAGENICITY:  
There is no data to indicate that any component present at greater than 0.1% will alter DNA.

## SECTION 12 - ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA:  
Contains ammonia or amines which may be toxic to aquatic life.

## SECTION 13 - DISPOSAL CONSIDERATIONS

This product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261, however, state and local regulations may be more restrictive. Coagulate the emulsion by the stepwise addition of ferric chloride and lime. Remove the clear supernatant and flush to a chemical sewer. Incinerate liquid and contaminated solids in accordance with local, state, and federal regulations.

## SECTION 14 - TRANSPORT INFORMATION

SHIPPING NAME:  
Not regulated. Not regulated for containers less than 450 liters (119 gallons). For containers greater than 450 liters and air: NA1993, Combustible liquid, N.O.S., (Petroleum Distillates), 3, III

## SECTION 15 - REGULATORY INFORMATION

All ingredients of this product are listed, or are excluded from listing, on the US Toxic Substances Control Act (TSCA) chemical substance inventory.

This product does not contain a chemical subject to the reporting requirements of SARA Title III, Section 313 (40CFR 372) above de minimis concentrations.

### STATE SPECIFIC REQUIREMENTS:

This product does not contain a chemical known to the state of California to cause cancer, birth defects or reproductive

**SAFETY DATA SHEET**

Page: 4 of 4  
Process Time: 7:07 am

Date Revised: 3/4/14

Date Printed: 2/16/16

harm, subject to the requirements of California Proposition 65.

STATE LISTED COMPONENTS      CAS NUMBER      STATE CODE      .

=====**SECTION 16 - OTHER INFORMATION**=====

REVISION DATE: 03/04/14

HMIS CODES: H	F	R	P
1 *	1	0	F